


ES8000 V-LOCK

Trimec Technology's new V-Lock introduces patented features that overcome the problems of door misalignment in 180 degree swinging doors and the problem of side load with 90 degree doors. This new high torque motorised lock can be concealed from view or surface mounted and has the worlds first fail-open motor locking mechanism which eliminates the need and cost of an additional key override.



- 
Side Load (Pre-Load) Capable
Lock will open with up to 15kg of side pressure (3 wire control required)
- 
Caters For Door Misalignment
+/- 3.5mm door misalignment tolerance.
- 
Power to Lock / Power to Open
Changeable on site
- 
High Torque Motorised Locking Operation
Overcomes locking problems caused by differential air pressure or dust seals.
- 
High Speed Operation
Unlocks in less than 0.2 sec.
- 
Surface Mount Accessory Kit
Ideal for 180° degree swing through Glass Door applications
- 
Multiple Orientation - Interior Doors
Can be mounted vertically or horizontally (For external doors ES8000 must be mounted horizontally)

Tested in accordance with: UL1034
 AS4145.2
 prEN12209-3
 prEN14846(E)
 CE COMPLIANT
 AS1905.1-1997 up to 4H FIRE RATING
 (Depending on type of fire door)

TRIMEC
 superior quality, design and innovation

An ASSA ABLOY Group company

ASSA ABLOY