

Installation Manual

TPS12-2.5SiBD



12V DC 2.5A Power Supply



POWERING
YOUR VISION[®]

TPS12Si
Series


Tactical
Technologies Pty Ltd



Designed & Manufactured



CAUTION



Equipment must be installed & serviced by suitably qualified service personnel in a restricted access area. There are no user serviceable parts inside.

Dangerous Voltage Inside !

Do not remove module covers

No user serviceable parts inside

General

This power supply is designed for indoor use only.

Utilising state-of-the-art voltage regulation techniques, the TPS12 Si Series provides clean 12.1V DC output to power your equipment, with an independent 13.8V DC channel for battery charging.

Available in 2.5 & 5A models, incorporating current limiting, short circuit shutdown and thermal overload protection, together with separate AC Fail & Low Battery relay outputs, the TPS12 Si Series has been designed and thoroughly tested to comply with stringent new Australian & New Zealand Electrical Safety and EMC standards.

The advanced design of the Si Series provides outstanding performance in the field, whilst maintaining significantly lower operating temperatures than most currently available linear supplies.

Also available as a standalone power module or factory fitted to steel enclosures with power distribution modules:

Order Part No: TPS12-2.5Si	12Vdc 2.5A Power Supply (192W x 132H x 90D)
Order Part No: TPS12-2.5SiB	12Vdc 2.5A Power Supply in steel enclosure (340Wx290Hx105D)

12Vdc 5A Models:

Order Part No: TPS12-5Si	12Vdc 5A Power Supply (242W x 132H x 90D)
Order Part No: TPS12-5SiB	12Vdc 5A Supply in steel encl. without distribution (340Wx290Hx105D)
Order Part No: TPS12-5SiBD	12Vdc 5A Supply in steel encl. with 10 way distribution (340Wx290Hx105D)

Connection

TPS12-2.5SiBD is fitted with a 10 Way power distribution Module (PDM1), providing 10 x 0.25A fused output terminals. The rating of these fuses may be changed (higher or lower current) provided that the total system current draw does not exceed 2.5A. The power supply will current limit and shut down if a total of 2.5 Amps load is exceeded.

Please take start-up / inrush current into account when configuring your system and take care to observe polarity when connecting a battery.

LAYOUT

TPS12-2.5Si



A	Output Terminals - connect to load (Observe Polarity)
B	AC OK LED
C	Mains Fail Relay Output
D	DC Output LED
E	Model Compliance & Date of Manufacture Label
F	Battery Terminals (Observe Polarity)
G	Low Battery LED
H	Low Battery Relay Output
I	Battery Connection Reversed LED

Warranty Statement

Tactical Technologies Pty Limited guarantees this product against defective parts and workmanship for a period of twelve (12) months from the date of purchase. If any defect appears during the warranty period, please return the goods to Tactical Technologies Pty Limited freight paid. The goods will be repaired or replaced, then returned.

Tactical Technologies Pty Limited assumes no liability for consequential or indirect damage and accepts no responsibility for repairing damage to products caused by misuse, careless handling or where repairs have been made by others. In the interest of ongoing product development, Tactical Technologies Pty Limited reserves the right to modify, vary or alter the design of this product without written notice.

Specifications

	TPS12-2.5SiBD
Output Voltage to Load	Factory set to 12.1 V dc
Output Current to Load	2.5A Max
Output Voltage to Battery	13.8V dc
Output Current to Battery	0.5A (500mA) Max
Output Channels	10
Output per Channel	250mA (0.25A)
Weight	5.5 kg
Dimensions	340W x 290H x 105D mm
Input Voltage	240V ac / 50 - 60Hz
Input Current	350mA (0.35A)
Safety Standards	AS/NZS 60950: 2003
EMC Standards	AS/NZS CISPR 14.1:2003 2 C-Tick N645
Mounting	4 x 3mm mounting holes

Tactical Technologies Pty Ltd

ABN 13 066 744 661

Tel: +61 2 8822-1888 5 Butterfield St, Blacktown NSW 2148 Fax: +61 2 8822-1899

“ Changing The Way You Think About Power ! ”

